



TECHNICAL DATA

The Legendary AMERICAN WOOD OIL *RAINBOW PIGMENTS Original Coloring System

For: Hardwood floors – all interior woodwork – doors – table and bar tops - furniture & fine woodworking – bathroom cabinets & kitchen counter top

DESCRIPTION

The Legendary American Wood Oil, Rainbow Pigments are specially formulated pasta pigments to blend in The Legendary American Transparent Gold and Warm Grey . The variety of the color pigments allows to an up grade of different wood species and to adapt to the look and the trend the designer is looking for.

Water resistant :

It is recommended to finish the color coat of with The Legendary American Wood Oil Clear Seal. The American Wood Oil Clear Seal has an excellent water resistance. Great for use in water-related areas such as bathrooms and kitchens.

Composition:

Modified Tung-oil pasta pigments.

Drying and curing :

in combination with The Legendary American Wood Oil Transparent Gold and Warm Grey.

Colors :

* Bleached Oak: blend 1 pigment white (025cl) in

1 gallon Warm Grey (3,785)

* Drift Oak : blend 1 pigment of grey (025cl) in

1 gallon Warm Grey (3,785)

*White Wash : blend 2 pigment white (050cl) in

1 gallon Transparent Gold (3,785)

*Olive Grey : blend 1 pigment Olive grey (025cl) in

1 gallon Transparent Gold (3,785)

*Classic Brown: blend 1 pigment brown (025cl) in

1 gallon Transparent Gold (3,785)

* Smoked Oak: blend 3 pigments brown (075cl) in

1 gallon Transparent Gold (3,785)

*Wengé Tone : blend 3 pigments black (075cl) in

1 gallon Transparent Gold (3,785)

A personal color can be achieved by using more or less pigments in 1 gallon (max. 4 pigments in 1 gallon) or mixing different pigments in 1 gallon.

Finish off with The Legendary American Wood Oil Clear Seal (original concept), or Finish off with The Legendary American Wood Oil Hard Wax Oil (traditional concept) Finish off with The Legendary American Wood Waterbased Finish (hybrid concept)

Coverage:

On smooth surfaces, approximately 40-60 square meter per gallon (3,875 L); on rough surfaces, 25-35 square meter per gallon (3,875 L). Mixed in Transparent Gold or Warm Grey This rates will depending upon the porosity of the surface

Packaging/Containers:

Available in 1/2 pints (025cl)

Restrictions:

Proper ventilation and adequate air circulation must be provided when using any wood finishing materials. A lack of cross-ventilation (air exchange) provides less free oxygen, slowing the drying process. It is not recommended to use the material in non-ventilated area. It is the oxygen molecules in the air that interact with the material, creating a chemical reaction causing the film to dry. Therefore the better the ventilation the quicker the film obtains its final hardness and other chemical resistance.

Not intended for exterior surfaces.

For exterior use The Legendary American Exterior Wood Oil.

TECHNICAL DATA

These products are in compliance with The Legendary American Transparent Gold and Warm Grey

formulation is product number

TB5998: white TB5997: gray

TB5996:cherry TB5999 :brown

TB6023 :black TB6029: tile red

TB6030: olive gray TB6028: belgian beige

TB6057: mahogany

AMERICAN WOOD OIL RAINBOW PIGMENTS

For: Hardwood floors – all interior woodwork – doors – table and bar tops - furniture & fine woodworking – bathroom cabinets & kitchen counter top

Cleanup and Disposal :

Clean brushes and equipment with mineral spirits.

Danger: Rags, steel wool, lambswool, waste, or any other materials soaked with The Legendary American Wood Oil for hardwood floors, doors, tables, bartops, furniture may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool, lambswool, waste or any other material in a sealed, water-filled metal container.

Dispose of empty cans or unused portion in accordance with local, state and federal regulations. Close container when not in use. Material Safety Data Sheet (MSDS) available upon request.

Physical and Chemical Data:

Drying Time: Approximately 8 - 12 hours, depending on the temperature and humidity.

The product should be applied at room temperature (min 16°C) and at normal air humidity (55 to 75%)

may react with strong oxidizing agents, such as chlorates, nitrates, peroxides etc

Vapor Density (Air=1): NDA

Boiling Point: 139°-199°C (281-390F)

Shelf Life: At least two years in closed original containers at room temperature.

Vehicle Type:., tung oil

APPLICATION

Proper surface preparation is the key to maximum finish performance.

surface preparation :

It is very important that the surface to be clean of all dirt, , loose wood fibres and other foreign matter. Previously finished wood should be stripped to bare wood.

(final sanding with 80-100 disc to open the pores for maximum penetration)

Vacuum and remove remaining dust with well wrung cloth. Surfaces must be structurally sound and absolutely dry.(Moisture content in the wood must be below 10%)

Application of Coating:

Stirring: Stir slowly with Transparent Gold or Warm Grey before and during application

Methods: Optimal results can be obtained by using a cotton cloth.

Wipe on the color in the direction of the grain, let it sink in for 5-10 minutes. Take off the surplus with a clean cotton cloth.

Allow to dry for about 8-12h before applying a finish coat . Sanding between coats is possible but not necessary.

Number of Coats:

Used for a primer, tone coat: only 1 coat

Precautions:

Even though the recommended dry time is

8-12 hours. The Legendary American Wood Oil

Transparent Gold and Warm Grey are hardened after 48 h and resistant to furniture removal.

Completely cure in 30-90 days

AVAILABILITY

The Legendary American Wood Oil

Transparent Gold is sold in the EU.

For a list of distributors and dealer locations, please have a look at our website :

www.americanwoodoil.com

WARRANTY

If this product does not perform as stated on the label after you apply it according

to label directions American Commercial Applications .Incorporated will either

replace this product or refund its purchase price, at its option. American Commercial

Applications Incorporated disclaims all other implied or expressed warranties and will not

provide or pay for labor for removal or application

of the product. This warranty excludes all incidental or consequential damages. This warranty gives you

specific legal rights, and you may have other rights which vary from state to state

MAINTENANCE

Easy maintenance. The Legendary American Wood

Oil penetrates deeply into the wood grain

and forms a protective yet elastic finish against

foot traffic, common household spills, and daily use.

We recommend for maintenance The Legendary

American Wood Oil Cleaner: a high quality

vegetable cleaner, completely biodegradable

TECHNICAL SERVICES

For additional technical information,

product line, color samples, and

liquid product samples, see your specialized

Legendary American Wood Oil Dealer

or contact us : info@americanwoodoil.com

Please check our website for photo's and video's :

www.americanwoodoil.com



European Factory Agency

Bredestraat 4, 2000 Antwerp, Belgium

Tel : +32 (0) 3 366 24 34 / Fax : +32 (0) 3 321 62 77

website : www.americanwoodoil.com / e-mail : info@americanwoodoil.com

