

## General Description

**Junckers PRO SEAL** is a primer designed for professional use in combination with **Junckers High Performance Commercial** or **Junckers HP SPORT**.

Compared to similar products **Junckers PRO SEAL** contains solvents with milder odour and solvency power.

## Technical Data

<b>Product:</b>	Air-drying alkyd in low odour solvents.
<b>Package sizes:</b>	2.5, 5 and 10 litres.
<b>Appearance:</b>	Provides wood with a deep, warm glow.
<b>Coverage:</b>	10 m <sup>2</sup> per litre.
<b>Application tools:</b>	Brush, mohair roller, air/airless spray.
<b>Substrate temperature:</b>	Minimum 10°C.
<b>Dilution:</b>	<b>Junckers PRO SEAL</b> is delivered ready for use.
<b>Drying time:</b>	Sanding and recoating: 24 hours at 23°C, 50 %RH. Allow to dry thoroughly prior to overcoating.
<b>Cleaning of tools:</b>	<b>Junckers Thinner 007</b> .
<b>Storage:</b>	Lasts for 2 years if unopened and stored at 20°C. Once opened the product will start to form a skin and may harden in the can.

### System Recommendations

<b>High traffic areas:</b>	1 coat <b>Junckers PRO SEAL</b> 10 m <sup>2</sup> /ltr. + 2 coats <b>Junckers High Performance Commercial</b> 10 m <sup>2</sup> /ltr.
<b>Low traffic areas:</b>	1 coat <b>Junckers PRO SEAL</b> 10 m <sup>2</sup> /ltr. + 1-2 coat <b>Junckers PRO TECH</b> 10 m <sup>2</sup> /ltr.
<b>Sport:</b>	1 coat <b>Junckers PRO SEAL</b> 10 m <sup>2</sup> /ltr. + 2 coats <b>Junckers HP SPORT</b> 10 m <sup>2</sup> /ltr.

### Directions for Use

#### Untreated/sanded floors:

Ensure that the surface is absolutely clean, dry and free from dust, wax, grease, polish etc. Sand away wax, oil stains, lacquer residue etc.

Vacuum sanding dust. Apply **Junckers PRO SEAL** and allow to dry.

Sand with fine paper grain 150-180 longitudinally to the fibres of the wood before applying further coats according to above "**System Recommendations**".

#### Previously lacquered floors:

Machine sand before lacquering with Junckers PRO SEAL. Use grain size 24-36 to strip old coats. Then remove abrasion marks with grain size 60-80. Finally, use grain size 100-120 to obtain a completely smooth surface. Vacuum sanding dust and wipe with a well wrung cloth and clean water. Then seal the floor as described under "**Untreated/Sanded floors**".

#### Important!

Before use of the product, read the label on the container carefully and observe the advised precautionary safety measures.

#### Important!

Stir well before use.

### Further information

#### Products:

- F 6.2 - **Junckers PRO TECH**
- F 7.5 - **Junckers Thinner 007**
- F 8.2 - **Junckers HP Sport**
- F 8.5 - **Junckers High Performance Commercial**