



## 22mm MULTI PLY STRUCTURED ENGINEERED FLOORING



Brushed & Oiled.

### **Appearance General**

#### **Colour:**

- Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

#### **Grain:**

- Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance

#### **Variations Within Species And Grades:**

- Considerable variation among boards in colour and grain texture.

#### **Specification:**

- Grade: Rustic
- Oak origin: Russia
- 22mm x 189 x 1830mm, 6mm top veneer
- 2 starter boards
- Pack Size: 1.3835 M2
- Oil : 2 coats
- Oil: Treffert, German brand
- Plywood species: poplar and hardwood mixed
- Adhesive: Melamine glue, China made, E1 environmental friendly
- FSC/PEFC certificate: No
- Janka score: 1360 'medium hardness'

### **Workability**

#### **Installation:**

- Professional recommended

#### **Sanding:**

- Good if the correct sanding sequence is followed

#### **Installing methods allowed:**

- Floating
- *Nailing on to Wooden Sub-Floor*
- Gluing on to Wooden or Concrete Sub-Floor
- Direct to joist

#### **Must never do:**

- Must not be laid in bathrooms

#### **Features and Advantages:**

- Can be laid over under floor heating
- Can be sanded and re-finished
- Made 100% of natural wood
- Ensures excellent thermal and acoustic isolation
- Dimensional stability
- Floor can be laid in all residential areas (except those of high humidity)
- Elka Extras available – underlay, adhesives, finishing profiles & maintenance products. View these at [www.elkaflooring.com](http://www.elkaflooring.com).

See [www.elkaflooring.com](http://www.elkaflooring.com) for warranty information